

HL459

PRODUCT SPECIFICATION SHEET

HIGH PERFORMANCE LIQUID CHROMATOGRAPHY Isocratic System



HPLC
Isocratic System

HL 459



Upgradable



LCD Display



Flowcell



PC

Ideal for routine Isocratic separations and Quality assurance applications.

Our Economical HPLC systems are perfect for tight spaces and smart budgets.

Easily Upgradable to Gradient.

SALIENT FEATURES

- High performance Pulse free piston pump with low dead volume diaphragm type pulse damper.
- Variable wavelength UV-VIS Detector features high sensitivity with absorbance ranges from 0 to 3.0 AU.
- MS Windows® based software Elichrom® provides complete system control, Data Analysis and multiple reporting options.
- Self flushing, Pulse Damper with Pressure Monitoring.
- Connecting tubes available in Stainless steel and Bio Compatible PEEK materials.
- Easy exchange of the Flow cells, Injection loops allows using the system for all applications between Micro upto preparative HPLC.
- Self diagnostics functions for start up hardware checks.
- Easy operatable Manual Injection Valve.
- An Autosampler, Fraction collector, Solvent Recycler can be easily added.
- Tools to facilitate 21 CFR part 11 compliance.



Pharmaceutical



Pesticide



Research



Chemical



Fertilizer



Food & Beverages



Clinical



Academic

APPLICATIONS

- Laboratories that demand Accuracy, Precision & reliability.
- Drug discovery, Drug metabolism, Proteins and Peptides Separations.
- Quality control labs in Pharmaceutical industries .
- Method development in R&D labs.
- Academic Institutes.

SPECIFICATIONS

HD 469

VARIABLE
UV-VIS DETECTOR

SPECTRAL

Range	190 to 800 nm
Bandwidth	4 nm
Readability	0.1nm
Accuracy	± 0.5 nm
Repeatability	± 0.2 nm

LIGHT SOURCE

Deuterium Lamp (D₂) &
Tungsten (W) Halogen Lamp

DATA PROCESSING &
PRESENTATION

PC

PHOTOMETRIC

Range	0 to 3.0 AU
Drift	<2.0 x 10 ⁻⁴ AU/hr @254 nm
Noise	± 0.001 AU @254 nm, 1.0 sec. rise time
Sensitivity Range	0.001 AU to 3.000 AU
Readability	0.0001 Abs

DETECTOR

Silicon Photo Diode

PHYSICAL DIMENSIONS

Size (WxDxH) in mm	246* x 437 x 195
Weight (in kg)	Approx. 10

*Excluding 60 mm cell width

FLOW CELL

Type	Analytical
Path Length	10 mm
Volume	15 µl
Material	Stainless Steel

TIME INTERVAL

0.1, 0.2, 0.3, 0.4, 0.5, 1 & 2 sec.

PC CONNECTIVITY

USB Interface

POWER REQUIREMENT

90-260 V AC, 50-60 Hz, 1Φ,
125 VA Max.

FLOW RATE

Standard	0.01 to 10 mL/min
Optional	0.001 to 5 mL/min
	0.1 to 40 mL/min

PHYSICAL DIMENSIONS

Size (WxDxH) in mm	246 x 437 x 140
Weight (in kg)	Approx. 11

HP 464

PUMP

QTY 1

PRESSURE

Standard	0 to 6,000 psi (10mL SS head)
Optional	0 to 6,000 psi (5mL SS head)
	0 to 5,000 psi (5 & 10 mL/min PEAK)
	0 to 1,600 psi (40 mL/min SS or PEAK head)

FLOW ACCURACY

± 2 %

FLOW PRECISION

0.2 % RSD

FEATURES

Pressure Monitoring
Prime Purge Valve
Pulse Damper
LED Display
RS-232 Input

POWER REQUIREMENT

90-260 V AC, 50-60 Hz, 1φ, 70 VA Max.

ACCESSORIES SUPPLIED

With Instrument	Columns, Injector, Mobile Phase Filter, Prime Purge Syringe, Injection Syringe.
At extra Cost	Other Applicable Columns & SGE Syringe and Sonicator.

Celebrating 60 years
of our Journey



www.elico.co/60years



www.elico.co

ELICO®

An ISO 9001:2018 | 14001 | 27001 Certified Company

B-90, A.P.I.E., Sanathnagar, Hyderabad 500 018, Telangana., India
Tel +91 40 44451234 Fax +91 40 23771639 info@elico.co

Ahmedabad
ahm@elico.co
+91 98241 75321

Bengaluru
blr@elico.co
+91 99000 28741

Bhopal
bpl@elico.co
+91 99930 96876

Bhubaneswar
bbr@elico.co
+91 99371 12105

Chennai
chn@elico.co
+91 98402 65797

Cochin
kel@elico.co
+91 81291 84400

Delhi
del@elico.co
+91 98710 06104

Guwahati
gau@elico.co
+91 91211 77451

Hyderabad
hyd@elico.co
+91 99896 25457

Kolkata
kol@elico.co
+91 91211 77452

Lucknow
lku@elico.co
+91 91980 01666

Mumbai
mum@elico.co
+91 77100 96111

Patna
pat@elico.co
+91 91211 77450

Visakhapatnam
vtz@elico.co
+91 99899 94532

